


REMARKS

If there are any additional fees resulting from this communication not covered by the enclosed check, or if the check was omitted, please charge all uncovered fees to our Deposit Account No. 16-0820, our Order No. 33868.

Respectfully submitted,

PEARNE & GORDON LLP

By:


Suzanne B. Gagnon, Reg. No. 48924

526 Superior Avenue, East
Suite 1200
Cleveland, Ohio 44114-1484
(216) 579-1700

Date: March 3, 2003



MARKED-UP VERSION SHOWING CHANGES MADE

IN THE CLAIMS:

Claims 1-9 and 11-20 have been amended in the following manner:

1 1. (Amended) [Method] A method for determining a threshold value (O_{\max} , O_{\min} ,
2 O_{TR}) serving to limit [the] an output signal of a processing unit into which an input signal
3 has been fed, characterized in that [the] a level of the input signal is determined and that
4 the threshold value (O_{\max} , O_{\min} , O_{TR}) is set as a function of [that] the level of the input
5 signal.

1 2. (Amended) [Method] The method as in claim 1, [characterized in that] wherein
2 from the said level a mean level (I) is derived on the basis of which the threshold value
3 (O_{\max} , O_{\min} , O_{TR}) is set[, with preferably only ambient noise contained in the input signal
4 being factored in].

1 3. (Amended) [Method] The method as in claim 2, [characterized in that] wherein
2 the threshold value (O_{TR}) is set by a differential amount (TR_{\max}) above the mean level (I)
3 of the input signal[, said differential amount (TR_{\max}) preferably being equal to twenty
4 decibels].

1 4. (Amended) [Method] The method as in claim 2, [characterized in that] wherein
2 the mean level (I) is derived from the input signal s(t) along the following formula:

3

$$I = \frac{I}{T} \times \int_0^T |s(t)| \times dt$$

4 whereby an averaging function is performed over a time interval T [having a
5 duration of preferably five seconds].

1 5. (Amended) [Method] The method as in [one of the claims 1 to 4, characterized
2 in that] claim 1, wherein a maximum threshold value (O_{\max}) is established.

1 6. (Amended) [Method] The method as in claim 5, [characterized in that] wherein
2 the maximum threshold value (O_{\max}) is so selected as to be equal to an upper comfort
3 level of a hearing-impaired person.

1 7. (Amended) [Method] The method as in [one of the claims 1 to 6, characterized
2 in that] claim 1, wherein a minimum threshold value (O_{\min}) is established.

1 8. (Amended) [Method] The method as in claim 7, characterized in that the
2 minimum threshold value (O_{\min}) is so selected as to be equal to an output level that results
3 from an input level of [preferably] about 80 dB and the corresponding amplification at
4 that input level that is produced for a hearing-impaired person.

1 9. (Amended) [Method] The method as in [one of the claims 2 to 8, characterized
2 in that] claim 3, wherein the differential amount (TRmax) is adjusted along a

3 compression ratio for a hearing-impaired person.

1 11. (Amended) Application of the method per [one of the claims 6, 8 or 9] claim
2 6 for operation of a hearing aid by a hearing-impaired person.

1 12. (Amended) [System] A system for implementing the method per [one of the
2 claims 1 to 9] claim 1, characterized in that a processing unit is provided which receives
3 an input signal and which permits within the processing unit the determination of a
4 threshold value (O_{\max} , O_{\min} , O_{TR}) for the purpose of limiting the output signal, said
5 threshold value (O_{\max} , O_{\min} , O_{TR}) being adjustable as a function of the level of the input
6 signal.

1 13. (Amended) [System] The system as in claim 12, [characterized in that]
2 wherein from the level of the input signal a mean level (I) can be determined by
3 averaging[, preferably derived only from the ambient noise contained in the input signal].

1 14. (Amended) [System] The system as in claim [12 or] 13, [characterized in
2 that] wherein the threshold value (O_{TR}) can be adjusted to a point which by a differential
3 amount (TR_{\max}) is above the mean level (I) of the input signal[, said differential amount
4 (TR_{\max}) preferably being equal to twenty decibels].

1 15. (Amended) [System] The system as in claim 14, [characterized in that]
2 wherein the mean level (I) can be derived from the input signal s(t) by employing the
3 following formula:

$$I = \frac{1}{T} \times \int_0^T |s(t)| \times dt$$

5 where an averaging function can be performed over a time interval T [with a
6 duration of preferably five seconds].

1 16. (Amended) [System] The system as in [one of the claims 12 to 15,
2 characterized in that] claim 12, wherein it permits a maximum threshold value (O_{\max}) to
3 be established.

1 17. (Amended) [System] The system as in claim 16, [characterized in that]
2 wherein the maximum threshold value (O_{\max}) can be selected to be equal to [the] an upper
3 comfort level of a hearing-impaired person.

1 18. (Amended) [System] The system as in [one of the claims 12 to 17,
2 characterized in that] claim 12, wherein it permits a minimum threshold value (O_{\min}) to
3 be established.

1 19. (Amended) [System] The system as in claim 18, [characterized in that]
2 wherein the minimum threshold value (O_{\min}) can be selected to be equal to the mean
3 amplification value for a hearing-impaired person.

1 20. (Amended) [System] The system as in [one of the claims 13 to 19,
2 characterized in that] claim 13, wherein the differential amount (TR_{\max}) can be adjusted
3 corresponding to [the] a compression ratio for a hearing-impaired person.

IN THE ABSTRACT:

The abstract has been amended in the following manner:

1 [Here described are a] A method and a system for defining a threshold value
2 (O_{\max} , O_{\min} , O_{TR}) serving to limit the output signal or a processing unit which is fed an
3 input signal. [According to the invention, an] An input-signal level is determined and the
4 threshold value (O_{\max} , O_{\min} , O_{TR}) is set as a function of that input-signal level. By virtue
5 of the fact that the threshold value is set as a function of the input-signal level, i.e. in
6 adaptive fashion, it is also possible to limit transient noise whose level is well below the
7 maximum value of the threshold value. As a result, when the method or system [per this
8 invention] is applied in a hearing aid, the hearing comfort of the wearer of the hearing aid
9 can be significantly enhanced.